Application of AHP-DEMATEL and GMDH Framework to Develop an Indicator to Identify Failure Probability of Wave Energy Converter

Tilottama Chakraborty and Mrinmoy Majumder

School of Hydro-Informatics Engineering National Institute of Technology, Jirania, Agartala–799055 Tripura (W), India; tilottama86@gmail.com, mmamjumder15@gmail.com

Abstract

The objective of the present study is to develop an extensive indicator which can represent the probability of failure of the wave energy converters. The objective was accomplished by the adaptation of a two-step methodology. In the first step, MCDM methods were used to estimate the priority values of the factors relevant to the probability of failure of the converter. In the second step, GMDH model was implemented to predict the values of the indicators which are directly proportional to the probability of failure of the converter. The significant parameters were identified by their consideration in different case studies and their influence on converter efficiency. The soft-computation methods like AHP-DEMATEL and GMDH were used to find the relative priority values of the parameters and to develop an automatic framework for estimation of the indicator. The indicator was made directly proportional to the ability of the converter to failure probability of wave energy in a specific location. The results from the multi-method estimation model were validated with the help of Multi Linear Regression Equation and some real time case analysis. With an accuracy of above, 99% the ensemble MCDM-ANN model depicts a reliability which ensures the author of its wide application for the real benefits like cost reduction and efficiency maximization of converters in the utilization of the potential energy of the locations. The model has the potential to become a tool with which engineers can easily identify the failure tendency of wave energy converters in specific locations.

Keywords: Analytical Hierarchy Process (AHP), Decision Making Trial and Evaluation Laboratory (DEMATEL), Ensemble Modeling, Group Method of Data Handling (GMDH), Wave Energy Converter

1. Introduction

Rising population levels around the world combined with depleting energy resources, particularly in the form of carbon deposits, have contributed to increasing pressures on global energy supply. In order to mitigate shortages in global energy supplies, nations are increasingly turning to renewable energy sources as a sustainable and secure source of energy¹. As a proportion of total energy production the capacity for energy contribution from renewable sources as of 2015 was estimated at 27.7%, which represented approximately 58.5% of the net additions to global power capacities in 2014² Of the various sources of renewable energy wind, solar power and hydroelectric power remain the most dominant sources of this observed growth in renewable energy output.

A wave energy converter is a device for extraction of energy from waves and conversion of the extracted energy into useful energy. The high cost of conversion and low extraction from the converter are the major obstacles to wide scale implementation of wave energy production plants.

Location selection for wave energy converter can be defined as the determination of a location, where all factors are considered in terms of maximization of output with minimization of cost. Also, it might be the most important decision which will affect the success of a project. The reason is that a good location can give the best results in and for this the location selection is the top priority before any other decisions. It becomes very difficult to compensate for the negative influence of a bad location decision³.

Several types of wave energy converters are already in

works and their reviews on wave energy conversion have been published in book form, as conference and journal papers, and as reports⁴.

The problems with Wave Energy Converter (WEC) are that most of these works under specific wave climate⁵ and the power generation of theses converters are not only dependent on the resources but also in the sea states⁶.

Failure of the converter may cause due to the failure of structure ⁷. The major reasons for the failure of wave energy converters, which are also the cause of the high costs and low efficiency of the converters, were found to be wave breaking due to extreme events (and corrosion due to contacts with sea water ^{8,9}. These failures occur due to the converter location, as well as the type of converters used for extraction. Although there are various methods to analyze the feasibility of converters in certain locations¹⁰ most of these are subjective¹¹ and applicable only to specific locations or converters ^{5,12}.

This is why the present study aims to develop a single medium to estimate the probability of failure of a converter when installing in a location of interest. The objective of the present study is to develop an extensive indicator which can represent the failure probability of the converters.

2. Methods Adopted

The objective was accomplished by the adaptation of a two-step methodology. In the first step, Multicriteria Decision Making Method (MCDM) was used to estimate the priority values of the factors relevant to the probability of failure of the converter. In the second step, the same priority values were used to develop the model to identify the suitable converter for a location. In this regard, Group Method of Data Handling (GMDH) and MaxStat lite software was used.

An integrated Analytical Hierarchy Process (AHP) - Decision Making Trial and Evaluation Laboratory (DEMATEL) MCDM was used to estimate the priority values of the factors, relevant to identify the ideal converter for wave power generation.

2.1 AHP

The AHP is an MCDM method introduced by Thomas L. Saaty in 1980. It is based on the relative priorities assigned to each criterion's role in achieving the objective. In this method, the problem is broken down into its constituent elements with the best alternative usually being selected by making comparisons between alternatives with respect to each attribute. AHP is widely used for decision making problems like Evaluation of Renewable Energy Project ¹³, Energy- Aware Decision making ¹⁴, Project Quality Evaluation in Construction Engineering ¹⁵, Power System ¹⁶ and Wind Energy ¹⁷.

2.2. Decision Making Trial and Evaluation Laboratory (DEMATEL)

The AHP-DEMATEL method originated from the Geneva Research Centre of the Battelle Memorial Institute ¹⁸ and is especially pragmatic for visualizing the structure of complicated causal relationships. The method is applied in the determination of environmental performance ¹⁹, developing models for improving the performance of solar farms ²⁰ and evolution of the risk of failure ²¹.

 Table 1. Factors which influence the failure of a wave

 energy converter

Parameters	Type of
	Impact
Locational Aspects	
Significant Wave Height (W_1)	В
Wave Amplitude(W ₂)	В
Wave Period (W ₃)	В
Depth of the Ocean (W_4)	NB
Shipping Density (W_5)	В
Percentage of Regular Waves (W ₆)	NB
Direction of Wave (W_7)	NB
Average Wave Power Level of the Sea (W_8)	В
Corrosion (W ₉)	В
Survivability (W ₁₀)	NB
Design Aspects	
Size and Shape (Diameter, Draft, Displace-	В
ment, Stroke Length, Height) (W_{11})	
Mass of the Buoy (W ₁₂)	В
Thickness of the Material Used (W ₁₃)	В
Efficiency of Wave Rotor/Generator (W_{14})	NB
Efficiency of Turbine (W ₁₅)	NB
Efficiency of Energy Storage System (W ₁₆)	NB
Efficiency of Hydraulic System (W ₁₇)	NB
Power Conversion Efficiency at Constant or	NB
Nearly Constant RPM (W ₁₈)	

Two different types of parameters Table 1 were considered. Beneficiary (B) parameters vary directly

with the objective equation and non-beneficiary (NB) parameters increase with decreases in the magnitude of the objective function.

3. Detailed Methodology

The parameters were selected from the literature survey.

AHP-VIKOR was used as the MCDM method to find the priority value of each parameter.

The Group Method Data Handling (GMDH)²¹ and MaxStat lite software were used as the predictive method for developing the model in the present study.

3.1 Selection of Criteria *3.1.1 Efficiency Potential*

The commonly used equation for calculating the power potential, as proposed by Pontes et al. (1995) and Tucker and Pitt (2001), is given in Equation 1

$$P_{\rm w} = \frac{pg^2}{64\pi} T_{\rm e} H_{\rm s}^2 \tag{1}$$

Where, $P_w =$ average wave power; $H_s^2 =$ significant wave height; $T_e =$ peak period; $\rho =$ density of water; and g = acceleration due to gravity.

As H_s squared is directly proportional to Pw, the efficiency potential or location with a high magnitude wave height will have a higher level of conversion efficiency. The relative score was calculated by Equation 2

(2)

$$RS = \left(\frac{R}{MaxR}\right)^{-1}$$

Where, R = 1, 2,....,7; Max (R) = 7

3.1.2 Cost Potential

The cost potential of parameters depends on the proportionality of the parameter to the mooring cost or the cost required holding the converters in place.

The score of the parameters for the cost potential was calculated by Equation 3; here if ΔC is the difference in cost for two different locations and ΔHs is the change in the wave height, then the cost potential of wave height can be represented by Equation 3.

$$C = \frac{\Delta C}{\Delta H} \tag{3}$$

The general equation for the estimation of the cost potential for the parameter is depicted in Equation 4.

$$C = \frac{\Delta C}{\Delta P} \tag{4}$$

Where, ΔP is the change in the magnitude of the parameter with respect to locations.

3.2 Selection of Alternatives

Eighteen different alternatives Table 1, based on location and design factor, were selected for the present investigation from the survey of the literature and expert's survey.

3.3 Development of the Model

The output of the model was the index value which is the ratio of the beneficiary factors and the non-beneficiary factors for the failure mode of a converter. The input to the model consisted of the eighteen factors Table 1. The index value was calculated with help of the equation 5.

$$Index = \frac{\Sigma W_n B_n}{\Sigma W_m N b_m}$$
(5)

where, W_n = weights of the parameter of positive influence. W_m = weights of the parameter of negative influence B_n = value of the beneficiary parameters Nb_m = value of the non-beneficiary parameter

The performance of the two models was analyzed by Mean Absolute Error (MAE) ²², PBIAS ²³, Correlation (R) ²³, MRE ²⁴ and RMSE ²⁵.An Equivalent Performance Index (EPI) was prepared to represent the performance of the models (Eqn.6). The model output is directly proportional to model efficiency.

$$EPI = \left\{ \frac{R_{ts}}{MAE_{ts} + MRE_{ts} + RMSE_{ts} + PBIAS_{ts}} * 0.6 \right\}$$
(6)
+
$$\left\{ \frac{R_{ts}}{MAE_{tr} + MRE_{tr} + RMSE_{tr} + PBIAS_{tr}} \right\}$$

Where, I_{ts} = Model output value for the testing model I_{tr} = Model output value for the training model

Two steps were involved in the calculation of EPI. In 1st step, the values of Mean Absolute Error (MAE), PBIAS, Correlation (R), MRE and RMSE for both the testing and training phase were calculated for each model. In 2nd step, the EPI were calculated for each model. As the model is directly proportional to the EPI value, so the maximum EPI shows the best model among the two developed model. Application of AHP-DEMATEL and GMDH Framework to Develop an Indicator to Identify Failure Probability of Wave Energy Converter

3.4 Case Study

The failure probability of two converters, Pelamis ²⁶ and Mighty Whale ²⁷, were analyzed for three different locations Figure 1. The power potential per meter of wave crest of 20 KW was found in Location 1 (10.5° N, 75.5°E), 15.90 KW in location 2 (15.3°N, 73.78°E), 11.81 KW in location 3 (17.09°N, 73.8°E) using the wave power potential equation [1].

4. Results and Discussion

The study results can be divided into three parts. The results from MCDM, from developed model and from case study which are depicted in 4.1, 4.2 and 4.3.

4.1 Relative Weights (AHP-DEMATEL)

The priority values, as determined by the MCDM method is depicted in Figure 2.



Figure 2. Rank of the parameters as per the priority value found from the AHP-DEMATEL MCDM meth.

As per the priority values as determined by the MCDM method (Figure 2), significant wave height (W_1) and Efficiency of Energy Storage System (W_{16}) were found to be the most important and least important parameters. So, it shows that significant wave height (W_1) is the most influential parameter as per the study objective.



Figure 1. Location map for the present study objective.

4.2 EPI Value

Table 2 shows the EPI of the two different developed models i.e. model developed by GMDH and Model developed by MaxStat Lite Software.

Table 2.Two developed model and thecorresponding EPI values

Model Developed by GMDH			
	Training	Testing	EPI
PBIAS	3.73264x 10 ⁻¹⁴	0.054635	42.3831
MRE	-0.00016	-0.00017	
MAE	0.007055	0.008639	
RMSE	0.009252	0.011669	
CORRELATION	0.997377	0.994987	
Model Developed by MaxStat Lite Software			
	Training	Testing	EPI
PBIAS	0.115423	0.25562	4.19166
MRE	0.002256	0.001089	
MAE	0.023888	0.015995	
RMSE	0.02589	0.06053	
CORRELATION	0.998562	0.992159	

Between the two different models, model developed by GMDH was found to have the maximum EPI i.e. 42.3831. So, the EPI value (Table 2) shows that the model developed by GMDH is best between the two models.

4.3 Case Study: Index value of three different locations with two different converters is showing in Figure 3.

It can be seen from the Figure 3 that Location-1 having the highest potential where Pelamis converter has lower failure probability. Between the two converters, Mighty Whale was found to be the most vulnerable and Pelamis was found to be the least vulnerable.



Figure 3. Model output for three different locations predicted by the GMDH m.

5. Conclusion

The present study attempts to develop a new indicator represent the failure probability of the converters in a specific location. This model is made objective by the application of MCDM and cognitive with the help of GMDH and Statistical software. The best model was identified from the two different models having the same inputs and output. The model with the highest efficiency was found to have a correlation value of 0.9973, which shows the reliability of the model. As per the case studies, Pelamis has the lower failure probability in each of the location.

Although the model has the potential to become a tool with which engineers can easily identify the ideal wave energy converters in specific locations, this method has some limitations. The importance of the variables was estimated by the one single hybrid MCDM methods but may change if other MCDM methods are used. This shows that the model is dependent on the type of methods utilized to find the priority value of the parameters. These drawbacks can be mitigated if some uniform policies are adopted regarding the selection of method, criteria, and alternative while the indicator is implemented in a decision support system.

6. References

- 1. RoulaInglesi-Lotz. The impact of renewable energy consumption to economic growth: A panel data application. Energy Economics. 2016 January 31;53:58–63. Crossref.
- 2. RenPS. Renewables 2015 global status report. REN21 Secretariat: Paris, France, 2015.
- Kuo K.J., S.C.Chi, S.S. Kao. A decision support system for selecting convenience store location through integration of fuzzy AHP and artificial neural network. Computers in industry. 2002 February, 47(2), pp.199-214. Crossref.
- Antonio F. de O.F. Renewables 2015 Global Status Report. Renewable and sustainable energy reviews.2010 April;14(3):899–918.
- Veigas M, Lopez M, Iglesias G. Assessing the optimal location for a shoreline wave energy converter. Applied Energy. 2014 November;132:404–11. Crossref.
- 6. Keskin H. Okur C. A. An approach to wave energy converter applications in Eregli on the western Black Sea coast of Turkey. Applied Energy. 2014 December;135:738–47. Crossref.
- Adem A, Komurcu M.I. Assessment of wave energy resource of the Black Sea based on 15-year numerical hindcast data. Applied Energy. 2013 January;101:502–12. Crossref.

- Roxana T, Mallon F, Dias F, Reynaud E.G. The challenging life of wave energy devices at sea: A few points to consider. Renewable and Sustainable Energy Reviews. 2015 March;43:1263–272. Crossref.
- Cordonnier J, Gorintin F, De Cagny A, Clement A.H, Babarit A. SEAREV: Case study of the development of a wave energy converter. Renewable Energy. 2015 August; 80:40–52. Crossref.
- Soumya G, Chakraborty T, Saha S, Majumder M, Pal M. Development of the location suitability index for wave energy production by ANN and MCDM techniques. Renewable and Sustainable Energy Reviews.2016 June;59:1017– 1028. Crossref.
- 11. Dalton G.J, Alcorn R, Lewis T. Case study feasibility analysis of the Pelamis wave energy convertor in Ireland, Portugal and North America. Renewable Energy. 2010 February;35(2):443–55. Crossref.
- 12. Pasquale P, Camporeale S.M. A linearized model for estimating the performance of submerged resonant wave energy converters. Renewable Energy. 2008 April;33(4):631–41. Crossref.
- Arif M, Al Badi M, Al Kahali A, Al Nabhani Y, Al Bahri A, Al Barhi H. 2014 October. Evaluation of renewable energy projects using multi-criteria approach. In Global Humanitarian Technology Conference (GHTC), IEEE. 2014 December.p.350–55
- 14. Benedicenti L. AHP and Soft Computing for Energy-Aware Decision-Making. In Advanced Information Networking and Applications Workshops (WAINA), 30th International Conference on IEEE.2016 March.p.273–75. Crossref.
- 15. H Shao, Fu H. Construction engineering project quality evaluation method based on fuzzy analytic hierarchy process. In Intelligent Transportation, Big Data and Smart City (ICITBS), International Conference on IEEE. 2015 December.p.228–31. Crossref.
- BhonsleJ.S., Junghare. A.S. Application of MCDM-AHP technique for PMU placement in power system. In Computational Intelligence & Communication Technology (CICT), IEEE International Conference on IEEE. February 2015.p.513–17.
- 17. Mogre R D, Amico F. A Decision Framework to Mitigate Supply Chain Risks: An Application in the Offshore-Wind Industry. IEEE Transactions on Engineering Management.

2016; 63(3):316-25. Crossref.

- Chia-WeiHsu C.W, Kuo T.C., Chen S.H, Hu, A.H. Using DEMATEL to develop a carbon management model of supplier selection in green supply chain management. Journal of cleaner production. 2013 October; 56:164–172. Crossref.
- Sang-Bing Tsai S.B, Chien M.F, Xue Y., Li L., Jiang X., Chen Q., Zhou J, Wang L. Using the fuzzy DEMATEL to determine environmental performance: a case of printed circuit board industry in Taiwan. PloS one.2015 January;10(6): 0129153.
- 20. Yi-ChunChen, Lien H.P, Tzeng G.H. Measures and evaluation for environment watershed plans using a novel hybrid MCDM model. Expert systems with applications. 2010 March; 37(2):926–38. Crossref.
- 21. Alibakhsh K, Ghalamchi M, Ahmadi MH, Ghalamchi M. GMDH algorithm for modeling the outlet temperatures of a solar chimney based on the ambient temperature. Mechanics & Industry. 2017;18(2): 216. Crossref.
- 22. Irurzun M. A, Chaparro MA, Sinito AM, Gogorza CS, Lirio JM, Nu-ez H, Nowaczyk NR, Böhnel HN. Preliminary relative palaeo intensity record and chronology on sedimentary cores from Lake Esmeralda (Vega Island, Antarctica). Latimag Letters. 2013;3(6):1–7.
- 23. Moriasi D.N., Arnold J.G, Van Liew M.W., Bingner R.L., Harmel R.D, Veith T.L. Model evaluation guidelines for systematic quantification of accuracy in watershed simulations. Trans. Asabe. 2007; 50(3):885–900. Crossref.
- 24. Rob J.Hyndman, Koehler AB. Another look at measures of forecast accuracy. International journal of forecasting. 2006 December;22(4):679–88. Crossref.
- Willmott C.J., Matsuura K. Advantages of the mean absolute error (MAE) over the root mean square error (RMSE) in assessing average model performance. Climate research. 2005; 30(1):79–82. Crossref.
- Ross H. Design, simulation, and testing of a novel hydraulic power take-off system for the Pelamis wave energy converter. Renewable energy. 2006 February;31(2): 271–83. Crossref.
- 27. Washio Y, Osawa H, Nagata Y, Fujii F, Furuyama H, Fujita T. The offshore floating type wave power device" Mighty Whale": open sea tests.