

# Automated Efficient Traffic Control System in Real Time Applications

V. Sai Prasanna\* and K. Kiran Kumar

Master of Technology in Embedded Systems, Department of ECM, KL University, Guntur - 522502, Andhra Pradesh, India; Prasannavallabhapuram470@gmail.com, kiran5434@kluniversity.in

## Abstract

**Background/Objectives:** This paper offers a clear traffic control system to pass emergency vehicles easily. In this paper to accomplish the raise of current innovation called Automated Efficient Traffic Control System: waiting time of emergency vehicles and also used to control the traffic lights. **Methods/Statistical Analysis:** This makes the utilization of Radio Frequency Identifier (RFID). This makes it very tough to take away or get broken. We use RFID reader TK-5530, and PIC16F877A. A device Micro-chip to take a gander at the RFID Tag related to the vehicle. **Findings:** If RFID tag takes a look at fits in with the stolen automobile the Information is transmits the usage of GSM SIM300 to the police manager further, whilst ambulance is coming near to the intersection, it will touch to activity controller inside of the intersection switch on the unpractised light. **Conclusion:** The module makes utilization of Zigbee detachable on CC2500 and PIC16F877A. Device Micro-chip for remote correspondences among the rescue vehicle or visitor controller. It is used to sense ambulance in multidirectional and also sense the ambulance to reach the junction to junction communication with the priority of the vehicle.

**Keywords:** Ambulance Detection, Data Collection of Vehicles, Micro Controller based System, Traffic Management

## 1. Introduction

INDIA is the second most crowded country worldwide and it is a quick developing economic system. Is seeing very high congestion issues in its cities. Infrastructure growth may be very less when contrasted with the development in measure of engines, because of space and charge imperative<sup>1</sup>. Additionally, an Indian site guest is non Lane based absolutely and clamorous. Its far necessities a few arrangements which do not used other countries. In efficient traffic control system traffic lights play a vital role in the traffic management system. Traffic lights are the communication devices that are placed on the intersection points and used to control the traffic jam on the roads. As of late wi-fi systems are broadly utilized as a part of the road transport on the grounds that the offer more value energy full options. The area like GSM, Zigbee and RFID<sup>2</sup>. RFID can be utilized in transport manipulates too offer free power full answers the issue. Of activity signal management can be explained by RFID

basically based framework. RFID is a remote field that perhaps the broadcast recurrence vitality to hold measurement s/w the RFID agenda and RFID follower. Some RFID structures will most straightforward operative of art in the reach a metric unit of length, equal to one hundredth of a metre. At the same time as others may fit for one hundred meters (three hundred toes) or greater<sup>3</sup>.

GSM electronic equipment could be a specialised sort of modem that acknowledges a SIM card over a membership to a cell administrator like a cell. AT charges place unit yearnings to administration modems. These orders originate from Hayes keen modems. The zigbee works at low power stop might be utilized inside the remaining measure of least the amount of task configurations to carry out predefined obligations. It operates in perception bands (868 mega cycles per second in Europe, 915 super cycles in United States of America and Australia, two. four rates in blow of the world) abstracts manual ante alter from Twenty Kilobits/second in the 868 mega cycles per second groups to 250 Kilobits-sec inside of the 2.4 rate

\*Author for correspondence

wave strip<sup>4</sup>. The zigbee utilizes eleven channels as a part of instance of 868/915 mega cycle per second frequency and sixteen directs if there should arise an occurrence of 2.4 GHz recurrence. It conjointly uses a pair of channel designs CSMA/CA and opened CSMA/CA<sup>5</sup>.

## 2. Proposed Method

From the present day problem segment, it could be visible that, present technologies are inadequate to cope with the issues of blockage automobiles, serious vehicle clearance, stolen auto discovery, et cetera. To clear up those troubles, we propose to enforce our smart web site efficient manage device. It particularly consists of three components. First element carries automated signal managing system. Right there, every automobile is readied with a RFID card. While it happens inside sort often RFID pursuer, it'll forward thee assurance most recent RFID pursuer. The RFID pursuer checks what numbers of cars have suppressed through for a specific duration and determine the congestion extent. For this reason, it units the inexperienced moderate span for that direction. 2nd aspect span for that automobile clearance. Right here, every emergency automobile carries ZigBee transmitter bore and the ZigBee receiver. Is probably done on the web page tourist's intersection. The bell can be exchanged ON even as the car is utilized for crisis reason. It delivers the sign through the ZigBee spammer to the ZigBee collector. It is going to roll out the intersection light to improvement to inexperienced. As quickly because the car goes through, the beneficiary now not gets the ZigBee arresting and the tourist's moderate is Grew to become to pink. It's far used to sense emergency clearance like ambulance, fire brigade VIP vehicles etc. In multidirectional and also sense the ambulance to reach the junction to junction communication with the priority of the vehicle. The 3r segment is for finding stolen vehicle discovery. Right here, while the RFID pursuer peruses the RFID label, it thinks about it to the posting of stolen RFIDs. In the event that a fit as a fiddle is resolved, it sends SMS to the badge administer allowance and become different the visitor's route direct to purple, simply so the car is made to prevent within the intersection and neighbourhood police can take appropriate motion. Posting of segments utilized inside of the test are CC2500 Radio Frequency recognizable proof, on chip PIC16F877A, RFID Reader- TK-5530 and SIM300 GSM module.

## BLOCK DIAGRAM




Figure 1. Traffic Control system

The above Figure1 describes the basic traffic control system. This system consists of the RFID reader, the in-built microcontroller, RFID tag and the LED displays.




Figure 2. Emergency vehicle clearance.

Figure 2 shows the overview of Emergency Clearance Vehicle. This system consists of the Zigbee Transmitter and the Zigbee Receiver along with the microcontroller and the LED displays.




Figure 3. Stolen vehicle detection.

Figure 3 shows the overview of Stolen Vehicle. This system consists of a GSM module which is used to send

the messages directly. This also consists of a RFID reader, microcontroller, RFID tag and LED displays.

## 2.1 Zigbee Bore CC2500

The CC2500 is a Radio recurrence detachable what's more, has Trans recipient, of which offers a clean manner to utilize RF discussion at 2 four GHz each CC2500 is added with the microcontroller (p.c. 16F877A), in corporate specific identity wide variety. According to Figure 1 this specific identification is primarily based on the registration quantity of the automobile. One of the maximum essential abilities is serial verbal exchange with none greater hardware and no greater coding<sup>6</sup>. For this reason, its miles a Trans receiver in light of the fact that it gives discussion in every directions, except handles one course. The microcontroller and continuously talk with the microcontroller transmission serial conversation. Rx metal stick of CC2500 is set up to Transmitter (RC6) of MC afterword Transmission metal stick of CXC2500 is establishment connect to Receiver metal stick of MC (RC7). Elite metal sticks are utilized to invigorate Tran collector. It is some separation works to address afterward acquire Theo information at 9600 baud price. Discern four.1.a indicates the picture of Tran's receiver. Here, we make use of CC2500 ZigBee approach furthermore, it has manual array of twenty meters<sup>7</sup>.

## 2.2 Microcontroller (PIC16F877A)

Fringe port oversees (%) 16F course of action has heaps of makes usage of when contrasted with other gathering. It executes anniversary instructing in significantly <2 hundred nano sec. It was 40 sticks and has 8K affairs anamnesis set and 368 byte insights measurements byte cycle it is anything but difficult to shop and ship UINs. At the intersection, it is spotless to spare substantial sort of crisis autos. Sooner than changing to unpractised, its miles used to fulfil the greater part of the circumstances. Straightforward intrude on circumstance gives the point of preference such as jump from one circle to a couple of other circle. It's far simple to trade whenever. It expends parcels considerably less ability and works through vehicle battery itself with no diverse equipment. Guardian

## 2.3 GSM Module SIM 300

Global System for mobile communication is best up with the MC. These permits to the pc to use the Global System


for mobile communication to allege end the versatile system. Those GSM have a lot of regularly acclimated offer cell net availability; masses often additionally could be acclimated for transmitting/accepting Short Message Service and Multi Media Service messages. Global System for mobile communication desires to aid a "prolonged AT charge set" for transmitting/accepting Short Message Service Global System for mobile communication price powerful answer for accepting SMS messages, due to accuracy the oblivious transfer accretion bulletin conveyance. Subscriber identity module3hundred is advised to international marketplace what's more, its miles a tri-band GSM motor. It absolutely works on freq. EGSM 900 MHz, DCS 1800 MHz and computer structures 1900 MHz SIM300 capabilities GPRS multi-slot elegance 10/ beauty eight (non-obligatory) furthermore, bolsters the GPRS coding technique. Global System for mobile communication is an especially bendy fitting and play cloister bandage GSM interact to RS232, it encourages abilities like noise information, Short Message Service, General packet radio service and adequate TCP/IP stack. Is Manage by agency of AT admonition (GSM 07.07, 07.05 and more noteworthy AT charges). Utilizes Alternate Current to Direct Current power connector with taking after appraisals Direct Current Voltage: 12V/1A<sup>8</sup>.

## 2.4 RFID Reader TK-5530

Radio Frequency Distinguishing proof (RFID) is an IT apparatus that transmits signs and manifestations without the region of genuine contraptions in wi-fi conversation. It 'smiles labelled underneath computerized identification etc that is properly mounted convention. The running of a RFID gadget is exceptionally basic. The contraption makes use of tags which can be connected to numerous additives to be tracked. The tags accumulate ability and tips apropos the abstracts of the fabricated from factors to be followed. The clairvoyant peruses the advice radio abundance and distinguishes the labels. The reception apparatus offers the appearance for the congenital ambit to address its abstracts to the pursuer. There are kind of RFID recommendations, dynamic afterward passive labels. The marks that don't make work of electricity are known as passive and they're pushed with the aid of a radio wire that lets in the tag to get to electromagnetic after-effects from a pursuer. At the opposite, live labels rely on upon power and that they accept built-in ability accoutrements that acquiesce it to address and receive get

hold of indicators from RFID pursuer. RFID esteem relies on upon transmit electricity; get hold of sensitivity and overall performance, reception apparatus, repeat, name presentations, environment. Commonly, Theo RFID assortment is journey a few centimetres to more than hundred meters. RFID pursuer work recurrence a hundred twenty five KHz with more than a few 10 cm<sup>9</sup>.

### 3. Results



**Figure 4.** Signal control system.


#### 3.1 Automated Efficient Signal Control Framework

In Figure 4 detachable, to test or to try a new way of doing something intent, we're use aloof RFID labels and RFID pursuer with recurrence a hundred twenty 5 KHz. RFID tag, whilst car comes quite close to the recipient will spam the best possible RFID Toward pursuer. Theo MC Contacted towards RFID pursuer depend Theo RFID labels study in Two minute period. For endeavouring out thought process, the depend is extra than 10, the unpractised mellow interim prepared to thirty seconds, if check amount is amongst five and 9, the unpractised moderate period is set to twenty sec. On the off chance that the subject is much lower than 5, the unpractised gentle length is set to 10 seconds. The red light period could be for 10 seconds and orange gentle length will presumably be for 2 seconds<sup>10</sup>.

#### 3.2 Vehicle Clearance in Real Time Applications

In Figure 5 detachable have 2 components, 1<sup>st</sup> perspective that is ZigBee transmitter is situated inside the crisis auto. While the transposition is squeezed, it'll Tune the sign. The signboard includes specific identification and protection code. This commentator have PIC16F877A MC

and ZigBee module. The microcontrollers have deliver directions and records to the ZigBee by means of happening one after another in time order correspondence. 2nd detail is the beneficiary this is situated at guest's shaft. It furthermore comprises of PIC16F877A MC and ZigBee module. The collector thinks about the assurance clave got aegis cipher begin in its collection data which is used to know the information of the vehicles. If it matches, then it's going to turn the inexperienced mild on. For checking out cause, we utilized brief reach RFID pursuer as a part of our model. To begin with, the recipient component is grown to emerge as on. The crimson and green sign and inexperienced sign may be on for ten sec length furthermore, orange light may be on for two sec length in a steady progression. Also, we include the RFID of baseborn auto into the appearance of RFID pursuer. At that point the sign will swing to purple for length of time of thirty seconds and a Short Message Service is won. Thirdly, inventory Twelve RFIDs towards assortment outfield RFID pursuer, including afterward the blooming moderate span exchange to thirty seconds. Fourthly, we convey a crisis auto passing on ZigBee communicator into the assortment of ZigBee recipient, after which Theo movement gentle will small to blooming until the collector gets the ZigBee communication<sup>11</sup>.



**Figure 5.** Ambulance junction to junction communication.

#### 3.3 Stolen Vehicle Identification

In Figure 6 detachable, for looking at reason, we analyse the specific RFID label study with the guide of Theo RFID pursuer to Theo baseborn RFIDs saved inside Theo computer. If fit observed, at that point the movement sign is at this moment swung to red for a breadth of thirty seconds. Moreover a Short Message Service is dispatched indicating the RFID manage through utilizing SIM300

Global System for mobile communication The LCD show embrace to demonstrate the at particular car<sup>12</sup>.




Figure 6. Stolen vehicle detection.

## 4. Conclusion and Enhancement

With programmed activity signal control in light of the movement thickness in the course, the manual exertion with respect to the activity policeman is spared. The whole framework is mechanized, it requires beneath human mediation. With stolen vehicle identification, the sign naturally swings to red, so the detective can make suitable move, in the event that he/she is available intersection. Additionally Short Message Service will be sent with the goal they can get ready to get the stolen vehicle at the following conceivable intersections. Crisis vehicles like emergency vehicle, fire trucks, charge to ability their destinations at the most punctual. On the off chance that they invest a considerable measure of energy in congested driving conditions, valuable existences of numerous individuals might in risk. With crisis car leeway, activity signal swings to green the length of the crisis vehicle is holding up in the activity intersection. The sign swings to red, strictly when the crisis vehicle goes through. Further upgrades should be possible to Theo model by testing it with best ambit RFID peruses. Additionally Global System for mobile communication can be set into the baseborn car location module, so the precise area of theft vehicle will be known. Presently, we executed framework by thinking of one as street of the activity intersection. It enhanced by developing to every one of the streets in a multi-street intersection.

## 5. References

1. Kalaivani R, Sudhagar K, Lakshmi P. Neural network based vibration control for vehicle active suspension system. *Indian Journal of Science and Technology*. 2016 Jan; 9(1):1-6.
2. Gokulan BP, Srinivasan D. Distributed geometric fuzzy multiagent urban traffic signal control. *IEEE Trans Intell Transp*. 2010 Sep; 11(3):714-27.
3. Li X, Shu W, Li M, Huang H-Y, Luo P-E, Wu M-Y. Performance evaluation of vehicle-based mobile sensor networks for traffic monitoring on vehicular technology. *IEEE Transactions*. 2009 May; 58(4):1647-53.
4. Elavarasi R, Senthil Kumar PK. An FPGA based regenerative braking system of electric vehicle driven by BLDC motor. *Indian Journal of Science and Technology*. 2014 Nov; 7(S7):1-5.
5. Li CH. Automatic vehicle identification system based on RFID. *Security and Identification in Communication (ASID)*. 2010 Jul; 281-4.
6. Sridharamurthy K, Govinda AP, Gopal JD, Varaprasad G. Violation detection method for vehicular ad hoc networking. *Security Commun Netw*. 2016 Feb; 9(3):201-7.
7. Abdoos M, Mozayani N, Bazzan ALC. Traffic light control in non-stationary environments based on multi agent Q-learning. *Proceedings of the 14th International IEEE Conference on Intelligent Transportation Systems*; 2011 Oct. p. 1580-5.
8. Yang W. A dynamic and automatic traffic light control system for solving the road Congestion problem. *WIT Transactions on the Built Environment (Urban Transport)*. 2006; 89:307-16.
9. Singh A, Kumar A, Goudar RH. Online traffic density estimation and vehicle classification management system. *Indian Journal of Science and Technology*. 2014 Apr; 7(4):508-16.
10. Ramya SB, Vasudevan SK, Aravind E, Karthick G, Harithaa S. Smart car design using RFID. *Indian Journal of Science and Technology*. 2015 Jun; 8(11):1-5s.
11. Murali Siva K, Parthasarathi V, Akshay B, Surya M, Vasudevan SK. Smart/efficient method to facilitate highway pedestrian protection. *Indian Journal of Science and Technology*. 2015 Sep; 8(21):1-4.
12. Sharma S, Pithora A, Gupta G, Goel M, Sinha M. Traffic light priority control for emergency vehicle using RFID. *Int J Innov Eng Technol*. 2013; 2(2):363-6.